

It's a better machine



YAMAHA 250
STREET



DS7

EUROPA

SPECIFICATIONS

PERFORMANCE	
Max. speed range	150-160 km/h (93-100 mph)
Climbing ability	24 degrees
Min. turning radius	2,300 mm (90.6 in.)
Min. braking distance	14 m @50 km/h (46 ft. @31 mph)
ENGINE	
Type	2-stroke, 5-port, Parallel Twin
Displacement	247 cc (15.07 cu. in.)
Bore & Stroke	54x54 mm (2.126x2.126 in.)
Compression ratio	7.1 : 1
Max. horsepower	30 hp @ 7,500 rpm
Max. torque	2.92 kg-m (21.1 ft.-lb) @ 7,000 rpm
Lubrication system	Autolube
Starting system	Primary kick starter
Transmission	5-speed gearbox
DIMENSIONS	
Overall length	2,040 mm (80.3 in.)
Overall width	835 mm (32.9 in.)
Overall height	1,085 mm (42.7 in.)
Wheelbase	1,320 mm (52.0 in.)
Min. ground clearance	150 mm (5.9 in.)
WEIGHT (Net)	138 kgs. (304 lbs.)
FUEL TANK CAPACITY	12 lit. (3.2 US gal.)
OIL TANK CAPACITY	2 lit. (2.1 US gal.)
TIRES front	3.00-18-4PR
rear	3.25-18-4PR

* Specifications subject to change without notice.

CARACTERISTIQUES

PERFORMANCES	
Vitesse max.	150-160 kms/h (93-100 mph)
Tenu en côte	24 degrees
Rayon de braquage min	2,300 mm (90.6 pouc.)
Distance au min. de freinage	14m @50 km/h (46 pie @31 mph.)
MOTEUR	
Type	2 cylindres, 2-temps, 5 orifices
Cylindrée	247 cm ³ (15,07 pouc. cu.)
Alésage et course	54 x 54 mm (2,126 x 2,126 pouc.)
Taux de compression	7,1-1
Puissance max.	30 C.V. @7,500 r.p.m
Couple moteur max	2,92 kgs-m (21,1 ft.-lb) @7,000 r.p.m
Système de lubrification	Autolube
Dispositif de mise en marche	Démarrreur à kick primaire
Transmission	Boîte à 5 vitesses
DIMENSIONS	
Longueur totale	2,040 mm (80,3 pouc.)
Largeur totale	835 mm (32,9 pouc.)
Hauteur totale	1,085 mm (42,7 pouc.)
Empattement	1,320 mm (52,0 pouc.)
Garde au sol min	150 mm (5,9 pouc.)
POIDS (Net)	138 kgs (304 livr.)
CAPACITE DU RESERVOIR D'ESSENCE	12 litres (3,2 gal. de U.S.A.)
CAPACITE DU RESERVOIR D'HUILE	2,0 litres (2,1 qua. de U.S.A.)
PNUES Avant	3,00-18-4PR
Arrière	3,25-18-4PR

*Caractéristiques sujets à modifications sans avis préalable.